

1. Unique identification code of the product-type:
Light transmitting single skin profiled plastics sheets, in PC.
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)
ONDULI95 D56-035 - Thickness 8 / 10
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

- internal and external wall and ceiling finishes.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
ONDULINE ZA Schumann - Rue Descartes B.P.50035 59559 Comines Cedex (France)
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4.
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :

Not applicable.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

Not applicable.
9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
External fire performance	F Roof (NPD)	EN 1013:2013
Reaction to fire	B S1 d0	
Water vapour permeability	3,8 x 10 ⁻⁵	
Water/air permeability	CONFORME-PASS	
Release of dangerous substances	NPD	
Dimensional tolerances	CONFORME-PASS	
Shatter properties (safe breakability)		
as :		
- Small hard body impact resistance	CONFORME-PASS	
- Large soft body impact resistance (assembly)	NPD	
Mechanical resistance (Nm²)	156	
Flexural tensile strength (Nmm⁻²)	80	
Resistance to fixings	See installation guide	
Durability, as variation (after ageing) :		
- of yellowness index	19 (B0)	
- of light transmission	10% (B0)	
- on flexural strength for :		
flexural strength, and	≤ 10% (B0)	
flexural modulus	≤ 10% (B0)	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

S.POUDROUX

